BOLTON, MA

MALLARD LANE

SHEET INDEX

SHEET NUMBER	SHEET TITLE	LAST REVISED
SHEET C1.0	TITLE SHEET	3/11/2020
SHEET C1.1	EXISTING CONDITIONS PLAN	3/11/2020
SHEET C2.0	LAYOUT PLAN	3/11/2020
SHEET C3.0	GRADING & DRAINAGE PLAN	3/11/2020
SHEET C3.1	GRADING & DRAINAGE DETAILS 1	3/11/2020
SHEET C3.2	GRADING & DRAINAGE DETAILS 2	3/11/2020
SHEET C4.0	EROSION CONTROL PLAN	3/11/2020
SHEET C4.1	EROSION CONTROL DETAILS	3/11/2020
SHEET C5.0	UTILITIES PLAN	3/11/2020
SHEET C5.1	UTILITIES DETAILS	3/11/2020


RECORD INFORMATION

RECORD OWNER:

JAMES MORIN & KATHRYN LUM
307 CENTRAL ST, APT 331
HUDSON, MA

BOOK 58115 PAGE 346 PARCEL NUMBER: 002.C-0015.1

ZONING DISTRICT:
RESIDENTIAL



LEGEND

EXIST. FEATURE	DESCRIPTION	EXIST. SYM.	DESCRIPTION
	STREAMS/RIVERS	\Diamond	LIGHT POLE
	WETLANDS	6	TELEPHONE POLE
	LIMIT OF BUFFER ZONE		GUY WIRE
000000000000000000000000000000000000000	STONE WALL	~	HYDRANT
W	WATER LINE	***	SEWER MANHOLE
OW	EXISTING OVER-HEAD WIRES	<u>////</u>	WETLAND FLAG
100	EXISTING CONTOUR (INDEX)	WF A1	WEILAND FLAG
	· · · · · ·		CATCH BASIN
401	EXISTING CONTOUR (INTERMEDIATE)	₩V ⊠	WATER GATE VALVE
	EXISTING BUILDING/HOUSE	\triangleleft	FLAG POLE
TDEE LINE			SHRUB
TREE LINE	TREE LINE		
PROP. FEATURE	DECODIDATION	DDOD CVM	DECODIDITION
PROP. FEATURE	DESCRIPTION	PROP. SYM.	DESCRIPTION
PROP. FEATURE			DESCRIPTION
PROP. FEATURE	PROPERTY LINE	© ^{DMH−1}	
W		© ^{DMH−1}	PROPOSED STORM WATER MANHOL PROPOSED CATCH BASIN
	PROPERTY LINE HAYBALES		PROPOSED STORM WATER MANHOL
w	PROPERTY LINE HAYBALES PROPOSED WATER LINE	©DMH-1 ©CB-1	PROPOSED STORM WATER MANHOL
	PROPERTY LINE HAYBALES PROPOSED WATER LINE PROPOSED SANITARY SEWER PROPOSED STORM DRAIN	©DMH-1 ©CB-1	PROPOSED STORM WATER MANHOL
	PROPERTY LINE HAYBALES PROPOSED WATER LINE PROPOSED SANITARY SEWER PROPOSED STORM DRAIN PROPOSED BACK CAPE COD BERM	©DMH-1 ©CB-1	PROPOSED STORM WATER MANHOL PROPOSED CATCH BASIN PROPOSED FLARED END SECTION
	PROPERTY LINE HAYBALES PROPOSED WATER LINE PROPOSED SANITARY SEWER PROPOSED STORM DRAIN	©DMH-1 ©CB-1	PROPOSED STORM WATER MANHOL PROPOSED CATCH BASIN PROPOSED FLARED END SECTION PROPOSED RIPRAP
	PROPERTY LINE HAYBALES PROPOSED WATER LINE PROPOSED SANITARY SEWER PROPOSED STORM DRAIN PROPOSED BACK CAPE COD BERM	©DMH-1 ©CB-1	PROPOSED STORM WATER MANHOL PROPOSED CATCH BASIN PROPOSED FLARED END SECTION PROPOSED RIPRAP
	PROPERTY LINE HAYBALES PROPOSED WATER LINE PROPOSED SANITARY SEWER PROPOSED STORM DRAIN PROPOSED BACK CAPE COD BERM PROPOSED EDGE OF PAVEMENT	©DMH-1 ©CB-1	PROPOSED STORM WATER MANHOL PROPOSED CATCH BASIN PROPOSED FLARED END SECTION PROPOSED RIPRAP STANDARD TREE PINE TREE
	PROPERTY LINE HAYBALES PROPOSED WATER LINE PROPOSED SANITARY SEWER PROPOSED STORM DRAIN PROPOSED BACK CAPE COD BERM PROPOSED EDGE OF PAVEMENT PROPOSED UNPAVED ROAD	DMH-1 CB-1 FES O	PROPOSED STORM WATER MANHOL PROPOSED CATCH BASIN PROPOSED FLARED END SECTION PROPOSED RIPRAP STANDARD TREE
	PROPERTY LINE HAYBALES PROPOSED WATER LINE PROPOSED SANITARY SEWER PROPOSED STORM DRAIN PROPOSED BACK CAPE COD BERM PROPOSED EDGE OF PAVEMENT PROPOSED UNPAVED ROAD PROPOSED CONTOUR (INDEX)	DMH-1 CB-1 FES O	PROPOSED STORM WATER MANHOL PROPOSED CATCH BASIN PROPOSED FLARED END SECTION PROPOSED RIPRAP STANDARD TREE PINE TREE

PRELIMINARY

DUCHARME & DILLIS Civil Design Group, Inc.

CIVIL ENGINEERS • LAND SURVEYORS • WETLAND CONSULTANTS


JAMES MORIN & KATHRYN LUM 307 CENTRAL STREET, APT 331 HUDSON, MASSACHUSETTS


JAMES MORIN 307 CENTRAL STREET, APT 331 HUDSON, MASSACHUSETTS COPYRIGHT DUCHARME & DILLIS CIVIL DESIGN GROUP, INC 2020


		DATE:	
			3/11
		DESIGN	BY:
		DRAWN	BY:
		CHECKE	:D B

:: 3/11/20			TITLE SHEET MALLARD LANE
GN BY: JPL			BOLTON, MASSACHUSET
01 L	NO.	DATE	DESCRIPTION
WN BY:			
JPL			
CKED BY:			

JOB NO. 5293 DRAWING NO. 5293-TITLE SHEET NO.









INFILTRATION AREA B

NOT TO SCALE





INFILTRATION AREA A CROSS SECTION

NOT TO SCALE



INFILTRATION AREA B CROSS SECTION NOT TO SCALE





CULTEC INSPECTION PORT DETAIL

INFILTRATION AREA A

NOT TO SCALE

SCALE:

PRELIMINARY



www.DucharmeandDillis.com

092 MAIN STREET, P.O. BOX 428

OLTON, MASSACHUSETTS 01740

JAMES MORIN & KATHRYN LUM 307 CENTRAL STREET, APT 331 HUDSON, MASSACHUSETTS


> JAMES MORIN 307 CENTRAL STREET, APT 331 HUDSON, MASSACHUSETTS


COPYRIGHT DUCHARME & DILLIS CIVIL DESIGN GROUP, INC 2020

	DATE:		GR/	ADING & DRAINAGE DETAILS 1
l	3/11/20		OI V	
l	· ·			MALLARD LANE
l	DESIGN BY:			
l				BOLTON, MASSACHUSETTS
l	JPL	110		DECORIDE TO M
l		NO.	DATE	DESCRIPTION
l	DRAWN BY:			
l	JPL			
l	JPL			
l	CHECKED BY:			

FMM

JOB NO. 5293 DRAWING NO. 5293-GRADE BY SHEET NO.





- EROSION CONTROL MEASURES SHALL BE INSTALLED PRIOR TO ANY DISTURBANCE ON SITE.
- AREAS WHICH ARE NOT TO BE DISTURBED SHALL BE CLEARLY MARKED BY FLAGS, SIGNS, ETC. RETAIN EXISTING VEGETATION WHERE FEASIBLE. THERE SHALL BE NO STORAGE OF ANY KIND OF ANY CHEMICALS, PESTICIDES, FUELS AND OTHER POTENTIALLY TOXIC OR HAZARDOUS MATERIALS
- 5. NO DEBRIS, JUNK, RUBBISH OR OTHER WASTE MATERIALS SHALL BE BURIED ON THE SITE.
- 6. STUMPS AND OTHER WOOD DEBRIS SHALL BE DISPOSED OF IN ACCORDANCE WITH THE "POLICY ON THE DISPOSAL OF WOODWASTES" PUBLISHED BY THE DEPARTMENT OF ENVIRONMENTAL AFFAIRS, DATED AUGUST 14, 1987.
- 7. THE JOB SUPERINTENDENT SHALL BE RESPONSIBLE FOR THE INSTALLATION AND MAINTENANCE OF ALL EROSION AND SEDIMENT CONTROL

B. MAINTENANCE / PERFORMANCE STANDARDS:

ALL EROSION AND SEDIMENTATION CONTROL MEASURES SHALL BE INSPECTED WEEKLY AND AFTER EACH RAINFALL WITH AN ACCUMULATION OF ½" OR MORE. THE FOLLOWING ITEMS SHALL BE CHECKED IN PARTICULAR:

- THE SILT FENCE BARRIERS SHALL BE CHECKED REGULARLY FOR TEARS, DETERIORATION, AND UNDERMINING.
- ALL SEEDED AREAS SHALL BE CHECKED REGULARLY TO SEE THAT A GOOD STAND IS MAINTAINED. AREAS SHOULD BE RESEEDED AS NEEDED. THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION WHICH WILL PREVENT TRACKING OR FLOW OF MUD ONTO THE PUBLIC ROAD. THIS MAY REQUIRE PERIODIC TOP DRESSING WITH 2 INCH STONE AS CONDITIONS DEMAND AND OR CLEANOUT/REPLACEMENT OF STONE IF CLOGGING OR SEDIMENTATION OCCURS. ALL MATERIALS SPILLED DROPPED, WASHED, OR TRACKED FROM VEHICLES ONTO THE TOWN ROAD MUST BE REMOVED
- DAILY BY SWEEPING OR OTHER SUITABLE MEANS. 4. ALL AREAS ON SITE SUBJECT TO EROSION/SEDIMENTATION SHALL BE INSPECTED ON A REGULAR BASIS. ALL ITEMS SPECIFIED ON THIS AND OTHER PLANS SHALL BE INSPECTED TO VERIFY THAT THEY ARE OPERATING AS DESIGNED AND INTENDED. IT SHALL BE THE CONTRACTORS
- RESPONSIBILITY TO MAINTAIN AND REPAIR ALL STRUCTURES. 5. THE ENTIRE DRAINAGE SYSTEM SHALL BE INSPECTED ON A REGULAR BASIS AND PRIOR TO AND IMMEDIATELY AFTER ANY RAINFALL EVENT WHILE THE SITE IS DISTURBED.
 - CATCH BASINS SHALL BE INSPECTED WEEKLY TO ENSURE THAT THEY ARE WATER TIGHT, HAVE ADEQUATE SUMP CAPACITY, THAT OIL AND GAS TRAPS ARE IN PLACE. THEY SHALL ALSO BE INSPECTED AFTER EVERY SIGNIFICANT RAINFALL EVENT (I.E. A TWO—YEAR STORM EVENT OR GREATER) DURING THE FIRST THREE (3) MONTHS OF BEING PLACED IN SERVICE TO ENSURE THAT THEY ARE FUNCTIONING IN AN ADEQUATE FASHION. THE BASINS SHALL BE CLEANED WITH A VACUUM TRUCK WHEN 1/2 OF THE SUMP IS FILLED WITH SEDIMENT BUT NOT LESS THAN TWO (2) TIMES PER YEAR. AFTER THE FIRST THREE (3) MONTHS OF SERVICE THE BASINS SHALL BE INSPECTED NOT LESS THAN ONE (1) TIME PER YEAR TO ENSURE ADEQUATE FUNCTIONALITY. OIL/GAS TRAPS SHALL BE CLEANED WITH A VACUUM TRUCK AND MONITORED FOR HYDROCARBON BUILD UP SEMIANNUALLY
 - DEWATERING OF EXCAVATIONS DURING CONSTRUCTION SHALL BE ADDRESSED ON AN INDIVIDUAL BASIS AS NEEDED. IF TEMPORARY DEWATERING IS REQUIRED ON THE SITE OR IN CLOSE PROXIMITY TO THE 100 FT BUFFER ZONE, SEDIMENT BASINS SHALL BE CONSTRUCTED OR SILT TRAPS SHALL BE UTILIZED. SILT TRAPS AND SEDIMENT BASINS SHALL BE MAINTAINED DURING THE DEWATERING

C. TEMPORARY MEASURES:

- 1. PLACE EROSION CONTROL BARRIERS WITH STRAW WATTLES AS SHOWN ON THE EROSION CONTROL PLAN. 2. IF LOAM IS PLACED OUTSIDE OF THE NORMAL GROWING SEASON, SILT FENCE OR STRAW WADDLES SHALL BE PLACED BETWEEN THE LAWN AREA
- CONSTRUCT TEMPORARY STONE PAD AT EXIT TO THE SITE AS SHOWN ON THE EROSION CONTROL PAN.
- DURING DRY PERIODS, PROVIDE MEANS FOR MITIGATION OF DUST, SUCH AS WATERING OF EXPOSED AREAS.
- STOCKPILE LOCATIONS SHALL BE WITHIN THE PROPOSED LIMIT OF WORK. PLACE SILT FENCE AROUND ALL STOCK PILED AREAS. PILES LEFT FOR 21 DAYS OR MORE SHALL BE SEEDED OR COVERED WITH PLASTIC SHEETING. WASTE DISPOSAL RECEPTACLES AND TRAILERS WILL BE USED FOR THE DISPOSAL OF CONSTRUCTION DEBRIS, WHICH WILL BE REMOVED FROM THE
- SITE ACCORDING TO STATE, LOCAL AND FEDERAL GUIDELINES. CONSTRUCTION DEBRIS WILL INCLUDE PAVEMENT, UTILITY, EARTH AND BUILDING MATERIALS THAT CANNOT BE REUSED. THE RECEPTACLES WILL BE LOCATED ON-SITE AND COVERED. 7. PLACE SILT SACK INSERTS IN ALL PROPOSED CATCH BASINS AFTER CONSTRUCTED AND IN THE EXISTING LEACHING
- 8. IN ADDITION TO WHAT IS DEPICTED ON THE PLANS, SILT FENCE SHALL BE PLACED DOWN GRADIENT (UP-GRADIENT OF ANY STORMWATER APPURTENANCES, WETLAND BUFFER ZONES AND AREAS TO BE LEFT UNDISTURBED) TO EACH
- STRUCTURE DURING THE CONSTRUCTION PROCESS UNTIL THE DISTURBED AREA IS RESTORED. 9. THE DEVELOPER SHALL MAINTAIN ANY STORMWATER TREATMENT SYSTEMS USED TO TRAP SEDIMENT DURING CONSTRUCTION TO PREVENT SEDIMENT FROM LEAVING THE SITE AND SHALL REMOVE ALL SEDIMENT FROM ALL
- SYSTEMS WEN CONSTRUCTION IS FINISHED AND THE SITE IS STABILIZED. 10. ADDITION EROSION CONTROL MEASURES SHALL BE IMPLEMENTED DURING THE CONSTRUCTION PROCESS AS DEEMED NECESSARY BY THE TOWN OF BOLTON.

D. PERMANENT STABILIZATION:

- 2. SLOPES IN EXCESS OF 3 TO 1 SHALL BE HYDRO-MULCHED. LOAMED (4" MIN.) AND SEEDED SLOPES WILL BE PROTECTED FROM WASHOUT BY MULCHING OR OTHER ACCEPTABLE SLOPE PROTECTION UNTIL VEGETATION IS ESTABLISHED.
- 3. UNLESS OTHERWISE INDICATED HEREON ALL DISTURBED AREAS SHALL BE LOAMED (6" MIN.) AND SEEDED WITH AN APPROPRIATE MIXTURE OF GRASSES SUITABLE FOR THE AREA. AREAS NOT STABILIZED BEFORE THE END OF THE FALL PLANTING SEASON SHALL BE HYRDO-MULCHED AND
- SLOPES STEEPER THAN 3 TO 1 SHALL BE RESTORED WITH 4" OF LOAM (MIN.), SEED, FERTILIZER AND STAKED DOWN EROSION CONTROL BLANKET
- SIMILAR TO NORTH AMERICAN GREEN SC 150 BN. INSTALL IN ACCORDANCE WITH THE MANUFACTURERS INSTRUCTIONS. THE TEMPORARY MEASURES WILL NOT BE REMOVED UNTIL PERMANENT STABILIZATION HAS OCCURRED.
- 6. 4" OF MULCH SHALL BE APPLIED IN ALL LANDSCAPED AREAS SHOWN.


F. CONSTRUCTION SEQUENCE:

DURING THIS SEQUENCE ALL EROSION CONTROLS SHALL BE INSPECTED AND MAINTAINED. ALL DISTURBED AREAS SHALL BE STABILIZED BY SEEDING OR SODDING AS SOON AS POSSIBLE AFTER GRADING IS COMPLETE. EROSION BARRIERS SHALL BE REMOVED AFTER SLOPE STABILIZATION IS

- INSTALL EROSION AND SEDIMENT CONTROL MEASURES.
- DELINEATE AND FENCE UNDERGROUND INFILTRATION AREAS.
- EXCAVATED TO SUBGRADE IN CUT SECTIONS; BRING FILL SECTIONS TO SUBGRADE USING EXCAVATED SOIL. EXCAVATE UNDERGROUND INFILTRATION AREAS TO SUBGRADE USING LIGHT EARTH MOVING EQUIPMENT TO LIMIT SOIL COMPACTION. PREVENT
- STORMWATER FROM UN-STABILIZED AREAS FROM ENTERING UNDERGROUND INFILTRATION AREAS.
- INSTALL PROPOSED RETAINING WALLS. INSTALL BUILDING FOUNDATION, UNDERGROUND UTILITIES, AND BUILDING PADS. UTILITIES INCLUDE DRAINAGE SYSTEM, WATER AND ELECTRICAL. INSTALL UNDERGROUND INFILTRATION AREAS. EXCAVATE AND REPLACE ANY IMPERVIOUS SOILS TO A DEPTH OF TWO (2) FEET BELOW THE INVERT
- OF THE SYSTEM AND REPLACE WITH PERVIOUS SOILS. SCARIFY SYSTEM INVERT WITH ROTARY TILLER OR DISC HARROWER AND SMOOTH WITH LEVELING DRAG, OR EQUIVALENT GRADING EQUIPMENT, PRIOR TO PLACEMENT OF UNDERGROUND INFILTRATION AREA PER CONSTRUCTION DETAILS.
- PLACE COMPACTED BASE GRAVEL FOR THE PAVED AREAS: ROUGH GRADE AREAS TO BE LOAMED AND SEEDED. BRING ALL GRADES AND COVER TO FINAL GRADE. INSTALL PAVEMENT, CURBING AND SIDEWALKS.
- FINALIZE GRADING, LOAM, SEED AND MULCH DISTURBED AREAS. 11. PLANT TREES, SHRUBS AND GROUND COVER AS INDICATED ON PLANS.

G. DEWATERING:


- THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEWATERING DURING CONSTRUCTION.
- DEWATERING SHALL BE PERFORMED TO ACHIEVE CONSTRUCTION OF FOOTINGS, FOUNDATIONS, PAVEMENTS, AND OTHER SUBSURFACE UTILITIES AND APPURTENANCES IN DRY CONDITIONS.
- DEWATERING SHALL BE PERFORMED THROUGH THE USE OF IN TRENCH SUP PUMPS, WELLS, DRAINS AND OTHER ITEMS NECESSARY FOR CONSTRUCTION. CONTRACTOR SHALL FURNISH, INSTALL, MAINTAIN OPERATE AND REMOVE ALL DEWATERING DEVICES AND APPURTENANCES AS
- REQUIRED FOR CONSTRUCTION. SUCH ACTIVITIES SHALL BE INCLUDED IN THE CONTRACTOR BID. 4. THE FLOW FROM DEWATERING PUMPS SHALL BE DISCHARGED TO A SEDIMENTATION TRAP OR DEVICE PRIOR TO DISCHARGE TO A RESOURCE AREA.
- REFER TO THE DETAILS ON THIS PLAN. THE CONTRACTOR SHALL NOTIFY THE TOWN OF ALL DEWATERING ACTIVITIES AND COORDINATE THE LOCATION OF ALL DISCHARGE POINTS WITH THE TOWN PRIOR TO COMMENCING DEWATERING ACTIVITIES.



SILT SACK


NOT TO SCALE

NOTES:
1. LENGTH = 50' (SEE PLAN FOR LOCATION)



TEMP. CONSTRUCTION ENTRANCE DETAIL

NOT TO SCALE



SILTATION BARRIER NOT TO SCALE

PRELIMINARY

DUCHARME & DILLIS Civil Design Group, Inc.

CIVIL ENGINEERS • LAND SURVEYORS • WETLAND CONSULTANTS

PHONE: (978) 779-6091 FAX: (978) 779-0260 092 MAIN STREET, P.O. BOX 428 OLTON, MASSACHUSETTS 01740 www.DucharmeandDillis.com

JAMES MORIN & KATHRYN LUM 307 CENTRAL STREET, APT 331 HUDSON, MASSACHUSETTS

APPLICANT:


JAMES MORIN 307 CENTRAL STREET, APT 331 HUDSON, MASSACHUSETTS

SCALE:
COPYRIGHT DUCHARME & DILLIS CIVIL DESIGN GROUP, INC 2020

	DATE
	DESIG
	DRAV
	CHEC

OATE: 3/11/20		Е	ROSION CONTROL DETAI
DESIGN BY:			BOLTON, MASSACHUSETTS
01 L	NO.	DATE	DESCRIPTION
DRAWN BY:			
JPL			
CHECKED BY:			

JOB NO.
5293
DRAWING NO.
5293-EROSION
SHEET NO.
U4.



WATER MAIN IN TRENCH DETAIL NOT TO SCALE


5.0' MIN.

WATER PIPE

SEWER LINE

ALTERNATIVE
WATER PIPE LOCATION

WATER AND SEWER LINE CROSSING




NOTES:

1. SAND BACKFILL COMPACTED TO 95% DENSITY IS REQUIRED AROUND ALL WATER SERVICES.

PHONE: (978) 779-6091 FAX: (978) 779-0260


www.DucharmeandDillis.com


NOT TO SCALE



GRAVITY SEWER LINE TRENCH DETAIL

NOT TO SCALE





PRESSURE LINE W/ INSULATION TRENCH DETAIL

NOT TO SCALE

SEWAGE DISPOSAL CALCULATIONS:

HYDRAULIC LOADING:
THE SYSTEM HAS BEEN DESIGNED FOR TWELVE (11) BEDROOMS AT 150 GALLONS PER DAY PER BEDROOM = 1,650 GALLONS PER DAY.
(AGE RESTRICTED UNITS)

<u>SEPTIC TANK SIZE:</u>
AVERAGE DAILY FLOW 11 BEDROOMS = 1,650 G.P.D.
SEPTIC TANKS PROVIDED: 3,500 GALLON TANK (200% DAILY FLOW) FOLLOWED BY 2,000 GALLON TANK (100% DAILY FLOW).
PUMP CHAMBER PROVIDED: 2,000 GALLON TANK

PRIMARY LEACHING AREA:

DESIGN PERCOLATION RATE = 2 M.P.I. (SOIL CLASS I)

EFFLUENT LOADING RATE = 0.74 GALLONS/S.F.

LEACHING AREA REQUIRED = 1,650 GPD / 0.74 GPD/S.F. = 2,230 S.F.

TOTAL LEACHING AREA PROVIDED = (5) 75' TRENCHES, 2' WIDE x 2' DEEP (5 X 75 X 6) = 2,250 S.F.

TOTAL DESIGN FLOW = 2,250 S.F. X 0.74 GALLON/S.F. = 1,665 GALLONS.

RESERVE LEACHING AREA:
DESIGN PERCOLATION RATE = 2 M.P.I. (SOIL CLASS I)

EFFLUENT LOADING RATE = 0.74 GALLONS/S.F.

LEACHING AREA REQUIRED = 1,650 GPD / 0.74 GPD/S.F. = 2,230 S.F.

TOTAL LEACHING AREA PROVIDED = (5) 75' TRENCHES, 2' WIDE X 2' DEEP (5 X 75 X 6) = 2,250 S.F.

TOTAL DESIGN FLOW = 2,250 S.F. X 0.74 GALLON/S.F. = 1,665 GALLONS.


NITROGEN TREATMENT NOTES:

1. NITROGEN TREATMENT IS NOT REQUIRED SINCE THE UNITS ARE AGE RESTRICTED. SEE CALCULATIONS BELOW.

NITROGEN LOADING: LOT AREA / 40,000 SF X 440 GPD

184,472 SF / 40,000 SF x 440 GPD = 2,029 GPD OK 2,029 GPD > 1,650 GPD

SEE SEWAGE DISPOSAL SYSTEM PLANS FOR DESIGN DETAILS, CONSTRUCTION DETAILS AND PUMPING SPECIFICATIONS



TYPICAL SDS DETAIL

NOT TO SCALE

PRELIMINARY



092 MAIN STREET, P.O. BOX 428

OLTON, MASSACHUSETTS 01740

OWNER:

JAMES MORIN & KATHRYN LUM

307 CENTRAL STREET, APT 331

HUDSON, MASSACHUSETTS

APPLICANT:

JAMES MORIN

307 CENTRAL STREET, APT 331

HUDSON, MASSACHUSETTS

COPYRIGHT DUCHARME & DILLIS CIVIL DESIGN GROUP, INC 2020

SCALE:

DATE:
3/11/20
DESIGN BY:
JPL
DRAWN BY:
JPL
CHECKED BY:

FMM

UTILITIES DETAILS

MALLARD LANE
BOLTON, MASSACHUSETTS

NO. DATE DESCRIPTION BY

T:
JPL
BY:

JOB NO.
5293

DRAWING NO.
5293-UTILITIES

SHEET NO.

C5.1